

# RJ-3150

## 3" Mobile Printing Solution



### Top Features:

#### Compatible with Windows®

- Print from Windows PC's through the USB interface or wirelessly

#### Ready to Integrate with iOS® & Android apps

- Using Brother SDK (3<sup>rd</sup> party development required)

#### Portable Durable Handheld Design

- Designed to withstand even the harshest conditions. 1.8m drop tested, IP54 rating.

#### Full colour LCD display

- 3.3" colour LCD

#### Fast Print Speed

- Maximum 5ips (127mm/sec)(without peeler)

#### Low Maintenance costs

- Highly reliable direct thermal technology uses fewer moving parts than other printing technologies.

#### Low Consumable Costs

- No ink or ribbons to replace. The only consumable is the thermal media.

### General

<b>Carton contents</b>	Belt Clip Li-ion battery (PA-BT-001-A) Button type battery Documentation
<b>Language support</b>	UK, French, Dutch, German, Italian, Spanish

### Dimensions & Weights

<b>Without carton</b>	116(w) x 189(d) x 82(h)   680g (including battery)
-----------------------	--

### Built In Features

<b>Printing Method</b>	Thermal
<b>Printing speed</b>	Maximum 5ips (127mm/sec)(without peeler) Max 2ips(with peeler) (*Under Brother standard environment)
<b>Maximum print width</b>	72mm
<b>Print resolution</b>	203dpi
<b>Number of sheets per battery charge</b>	Li-ion battery: approx. 5300 labels (continuous print) *Under Brother standard environment)

<b>Interfaces</b>	USB Ver.2.0 (Full Speed) (mini-B). USB Host. Bluetooth Ver.2.1+EDR (Class 1. Wireless LAN IEEE802.11b/g/n (Infrastructure mode/Adhoc mode/Wireless Direct mode) IEEE802.11b/g/n (Infrastructure mode and Wireless direct mode:[b/g/n] / AdHoc mode:[b])
-------------------	--

<b>Operating system support</b>	Android 2.3 or later iOS 5 or later (requires 3 <sup>rd</sup> party app development using Brother SDK), information available at <a href="http://www.brother.eu/developer">www.brother.eu/developer</a>
---------------------------------	---

<b>Airprint support</b>	TBC
-------------------------	-----

<b>Printer commands</b>	Raster ESC/P P-touchTemplate ZPL emulation CPCL emulation
-------------------------	---

<b>Printer driver</b>	Microsoft® Windows Vista® Windows® 7 / Windows® 8 Windows® 8.1 Microsoft® Windows Server® 2008 / 2008 R2 / 2012 / 2012 R2
-----------------------	--

<b>Internal fonts &amp; sizes</b>	<ESC/P> Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot> Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot <P-touch Template> Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot
-----------------------------------	--

### Supplies

<b>RD roll type</b>	RD-PO8E5(Receipt) RD-PO9E1 (Label)
---------------------	---------------------------------------

### Optional Accessories

<b>Batteries</b>	Rechargeable Li-ion battery(PA-BT-001-A):7.2V Continuously Printing 5300 labels (*Under Brother standard environment)
<b>Shoulder Strap</b>	PA-SS-4000
<b>AC adaptor</b>	PA-CR-001 Single Cradle PA-BC-001 Single Battery Charger PA-AD-600 AC Adapter
<b>Car adaptor</b>	PA-CD-600CG Cigar lighter plug PA-CD-600WR Permanently wired